

A new slat for you in-ground slatted covers



OPAQUE PVC 84 SLATS

HODERNE AND SLEEK

- A new unique design on the market.
 Flexible joints and caps are black and distinguish of the slats' colour.
- The flexible "boat deck seal" joint also facilitates cleaning between the slats.
- A flat slat for a perfect finish on the water surface.
- Registered and patented model.

MATERIAL

- Extruded PVC slats without lead-based additive.
- The slats are UV-treated and have a good resistance to stains and organic deposits.
- Material compliant with age resistance requirements defined by standard NF T54-405-1: 2013.

(+) CAPS AND FLANGES

- Black welded caps for a perfect watertightness.
- The standard flange size is 2.50 cm. It is possible for adjustement at the time of installation to have flange of size S (-1 cm).



Your slats choice

All our slats are compliant with the NF P90-308 standard*.



Flexible joints and caps are black. Flange's colour is the same as the slat one.

*To comply with the French safety NF P90-308 standard, the slat must have a minimum width of 2.50 m.

USEFUL TO KNOW

Opaque PVC 84 slat is a new standard for the following configurations:

- In-ground automatic slatted covers.
- Pools up to 5.00 m wide.
- Rectangular pools (no cut-out).
- Corners radius of less that 15 cm.
- Opaque PVC 84 slat is not available for overflowing or mirror pools.
- Pushlock locking kit system only.

Why cover your pool?

- To reduce the water consumption by limiting the evaporation.
- To reduce the energy consumption.
- To make the cleaning easier & to reduce the use of chemical products.



DON'T FORGET

The pushlock locking kit of your slats ensure the safety of

of your slats er your pool.



can get drawned within less than 3 minutes; no type of protection will ever replace the vigilance and supervision of responsible adults.

Warranty: 3 year for opaque PVC 84 slats in accordance with your general sales terms.

Order form: to have slats correctly adjusted to the pool, it is essential to provide a drawing of the pool with measurements taken every 1 meter. In accordance with the French safety NF P90-308 standard, the gap between the inside of the pool and the edge of the cover must be less than 70 mm.

Time needed to close a pool measuring 5.00 x 10.00 m: 3 minutes to automatic opening or closing and 30 seconds for locking or unlocking the safety kits. Slats can be opened or closed by one person.

Use: for all seasons. For a proper functioning, maintain a constant water level corresponding to a normal filtration of the pool. It is essential to have a water level regulator. The water level has to comply with the technical notice.

Use limits: the installation of an automatic DEL slatted cover on overflow pools and/or with a stair along the length (detechable side stair) does not comply with the French safety NF P90-308 standard. Another safety device should be used in that case. Unless otherwise specified by the manufacturer, under water alarms are not compatible with DEL covers.

Wintering: the swimming pool must be wintered on the basis of its geographical location. Without lowering the water level, close the cover to its safety position and where applicable install a wintering net to protect the cover. If the water level is lowered so that the wall units are above the waterline, roll the cover in and secure the pool using a winter safety cover.

Packing list: for a swimming pool measuring 5.00 x 10.00 m. Slats: 4 packages: 5.10 x 0.39 x 0.11 m - 190 kg.

Manufacturer: DEL SAS - ZA La Croix Rouge 35530 Brécé - France / www.del-piscine.fr

FOR MORE INFORMATION PLEASE ASK YOUR POOL EXPERT

CF GROUP FRANCE - DEL SAS - ZA LA CROIX ROUGE - 35530 BRÉCÉ - FRANCE